



DUR-A-FLEX
INNOVATION FROM THE FLOOR UP

95 Goodwin Street East Hartford, CT 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2014

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) **Poly-Crete Aggregate: MD, TC, SL, HE, TE, and WR**

COMMON NAME **Sand/Cement Aggregate**

HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	3
	Flammability	0
	Reactivity	0
	Personal Protection	G

SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
Crystalline Silica (Quartz) ¹	14808-60-7	10mg/m ³	0.05 mg/m ³
		%SiO ₂ +2	
Portland Cement	65997-15-1	10mg/m ³	10mg/m ³
		Total Dust	Total Dust
Calcium/Magnesium Hydroxide	39445-23-3	15mg/m ³	10mg/m ³
		Total Dust	Total Dust

¹Crystalline silica can be a lung injury and cancer hazard. Do not breathe dust. May cause delayed lung injury. Long term exposure can cause silicosis, a respiratory disease which can result in a delayed, disabling, and sometimes fatal lung injury. Crystalline silica inhaled from occupational sources can from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.

T.S.C.A. Status - O.K.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	4,000°F	Specific Gravity (H ₂ O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point	3,000°F
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds	0 g/L		
Solubility in Water	INSOLUBLE		
Appearance and Odor	Naturally rounded sand. Various sizes. No odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	N/A	Flammable Limits	LEL	UEL
			N/A	N/A
Extinguishing Media	N/A			
Special Firefighting Procedures	N/A			
Unusual Fire and Explosion Hazards	N/A			

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	NONE KNOWN.
Incompatibility (Materials to Avoid)	Hydrofluoric Acid and powerful oxidizing agents		
Hazardous Decomposition or Byproducts	NONE KNOWN		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NONE KNOWN.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	NO	NO

Signs and Symptoms of Exposure Shortness of breath and reduced pulmonary function.

Health Hazards (Acute and Chronic)

ACUTE - NO SYMPTOMS.

CHRONIC - excessive inhalation of dust may result in respiratory disease such as silicosis, pulmonary fibrosis, etc. The IARC has evaluated in Vol.42 (monographs) that there is "sufficient evidence for the Carcinogenicity of crystalline silica dust to experimental animal" and "limited evidence" with respect to humans.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	Yes (Respirable Silica)	YES*Level 2A Grouping	NO

Medical Conditions Generally Aggravated by Exposure

Lung disorders and persons subject to eye irritation.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Expected to be slightly toxic by ingestion. If swallowed, induce vomiting immediately as directed by a physician. Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

OTHER HEALTH EFFECTS - Medical conditions which may be aggravated by exposure to this product include, conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases. Sensitization may occur by skin contact.

****NOTE**** persons with lung disorders or who are sensitized should not use this product.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH approved cartridge respirator.

Ventilation	Local Exhaust	To meet PEL requirements.	Special	None Known.
	Mechanical	Adequate to meet PEL requirements.		

Protective Gloves	Recommended.	Eye Protection	Recommended
-------------------	--------------	----------------	-------------

Other Protective Clothing or Equipment

Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57), and NIOSH Respirator Decision Logic. Maintain, clean and fit test respirators in accordance with OSHA regulations.

Work/Hygienic Practices Avoid creating and breathing dust.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud. Avoid creation of respirable dust

Waste Disposal Method

Dispose waste material in a sanitary land fill or as regulated by local, state and federal regulations.

Precautions to be Taken in Handling and Storing

Avoid creation of respirable dust. Take precaution against bag breakage.

Other Precautions None Known.

Prepared by Murty Bhamidipati - Chemist

PLEASE

NOTE

"The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



DUR-A-FLEX
INNOVATION FROM THE FLOOR UP

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2014

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) Poly-Crete Hardener: MD/SL, HF, and TF/WR

COMMON NAME Aromatic Isocyanate Blend

HAZARD RATING

0 = Least

1 = Slight

2 = Moderate

3 = High

4 = Extreme

Health 2

Flammability 1

Reactivity 1

Personal Protection G

SECTION II - PRODUCT COMPONENTS

CAS.#

OSHA PEL

ACGIH TLV

Polyisocyanate based on MDI

Trade Secret¹

NE²

NE

4,4-Diphenylmethane Diisocyanate

101-68-8

0.02 ppm

0.005 ppm

¹The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency.

²None Established

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point

392°F

Specific Gravity (H₂O = 1)

1.24

Vapor Pressure (mm Hg)

<10-5 @77F

Melting Point

NE

Vapor Density (AIR = 1)

8.5

Evaporation rate (Butyl Acetate = 1)

NE

Volatile Organic Compounds

0 g/L

Solubility in Water

Reacts slowly with water to liberate CO₂ gas

Appearance and Odor

Dark Amber liquid. Faint Aromatic odor.

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)

>400°F

Flammable Limits

LEL

UEL

NA

NA

Extinguishing Media

Dry Chemicals, CO₂, Universal Type Foam, Water Fog

Special Firefighting Procedures

Wear full protective equipment including self-contained breathing apparatus. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with H₂O used for cooling purposes.

Unusual Fire and Explosion Hazards

MDI vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. At temperatures greater than 400F, polymeric MDI can polymerize and decompose which can cause pressure build-up in containers. Explosive rupture is possible. Cold water can cool fire-exposed containers.

SECTION V - REACTIVITY DATA

Stability

Unstable

Conditions to Avoid

Stable

X

Keep containers closed when not in use.

Incompatibility (Materials to Avoid)

Water, amines, strong bases, alcohols, copper alloys and aluminum, zinc.

Hazardous Decomposition or Byproducts

Fire: Carbon monoxide, oxides of Nitrogen, traces of HCN, MDI vapors or aerosols.

Hazardous Polymerization

May Occur

X

Conditions to Avoid

Contact with moisture, other materials which react with isocyanates, or

Will Not Occur

temperatures above 400 F may cause polymerization.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	YES	Yes

Signs and Symptoms of Exposure Irritation and redness of skin and eyes. Breathing difficulty.

Health Hazards (Acute and Chronic) ACUTE Inhalation-can cause nasal and respiratory irritation, dizziness, headache, nausea.

Also, runny nose, sore throat, coughing, chest discomfort and reduced lung function. CHRONIC Inhalation-isocyanate sensitization can develop which can persist for weeks or years. Overexposure can cause lung damage which may be permanent. ACUTE Skin-isocyanates react with skin protein and cause irritation. CHRONIC Skin-prolonged contact can cause reddening, swelling, scaling, rash, blistering and skin sensitization. ACUTE Eye-tearing, reddening, swelling if untreated, corneal damage can result.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Respiratory disorders (asthma, bronchitis, emphysema, bronchial hyperactivity), skin allergies, eczema.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

Skin - remove contaminate clothing. Clean affected area with mild soap and water. If irritation or redness develops, seek medical attention.

INHALATION- move person away from source of exposure and into fresh air. If person is not breathing, give artificial respiration and seek medical attention immediately. If breathing difficulty develops, give oxygen and seek medical attention immediately.

Ingestion-DO NOT INDUCE VOMITING. Give 1 to 2 cups of milk or water to drink. Do not give anything by mouth to an unconscious person.

****NOTE** PERSONS WITH LUNG DISORDERS OR WHO ARE SENSITIZED SHOULD NOT USE THIS PRODUCT.**

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type) Use NIOSH approved respirator as outlined in 30CFR11 and 29CFR 1910.134 effective for solvent and diisocyanate vapors. Use SCBA or air-supplied respirators when TLV/PEL is exceeded.

Ventilation	Local Exhaust	Use in confined areas.	Special	Sensitized persons must not inhale vapors
	Mechanical	Must be sufficient to maintain area below established TLV/PEL.		

Protective Gloves	Neoprene rubber gloves.	Eye Protection	Splash proof goggles.
-------------------	-------------------------	----------------	-----------------------

Other Protective Clothing or Equipment

Use other protective equipment such as rubber aprons and a face shield if danger of splashing is possible. Eye wash station or clear water must be readily available. ENFORCE GOOD HYGIENE PRACTICES. No smoking or open lights in work area. Exposure to liquid, vapors, mists or fumes must be minimized. Use air supplied respirators in enclosed areas and when PEL/TLV is higher than established level.

Work/Hygienic Practices Launder contaminated clothing before use. Dispose contaminated leather shoes

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment, including respiratory equipment during clean-up. Absorb isocyanates with sawdust or another absorbent, shovel into unsealed containers, transport to a well-ventilated area. Decontaminate floor area.

Waste Disposal Method

Incineration in accordance with local, state, and federal regulations.

Precautions to be Taken in Handling and Storing Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Do not breathe aerosols or vapors. This material can cause asthmatic sensitization upon single exposure.

Other Precautions Exposure to vapors of heated MDI can be extremely dangerous.

Prepared by Murty Bhamidipati - Chemist

PLEASE

"The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."

NOTE



95 Goodwin Street, East Hartford, CT 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2014

SECTION I - IDENTIFICATION	HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	1
		Flammability	1
		Reactivity	0
		Personal Protection	B

Poly-Crete Resin: MD/SL, HF, and TF/WR all colors

IDENTITY (As Used on Label)

COMMON NAME POLYOL-PIGMENT BLEND

SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
Water	7732-18-5	N.E. ¹	N.E.
Polyester-ether polyol Blend	Proprietary ²	N.E.	N.E.
Glycol Ester Blend	Proprietary	N.E.	N.E.
Rutile Titanium Dioxide	13463-67-7	10mg/m ³	10mg/m ³
Inorganic Iron Oxides	1309-37-1	10mg/m ³	10mg/m ³
Carbon Black	1333-86-4	3.5mg/m ³ (dust)	5mg/m ³ (dust)

¹None Established

²The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	212°F	Specific Gravity (H ₂ O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation rate (Butyl Acetate = 1)	<1
Volatile Organic Compounds	0 g/L		

Solubility in Water Dispersable

Appearance and Odor Viscous Liquid. Color varies upon desired shade. Faint Aromatic Odor.

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	540°F	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media Foam, CO₂, dry chemical, water spray.

Special Firefighting Procedures

Wear full protective equipment including self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Combustion products may be toxic. Cool storage containers with water spray to prevent pressure build-up that may rupture the containers.

SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable X	

Incompatibility (Materials to Avoid) Strong Oxidants

Hazardous Decomposition or Byproducts Burning will produce toxic fumes

Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur X	

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	No	Yes	Yes

Signs and Symptoms of Exposure Irritation of skin..

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis.

CHRONIC - Repeated over-exposure may cause skin irritation, dermatitis and sensitization.

Sensitized persons may experience rapid irritation of skin upon exposure.

NOTE: Persons with lung disorders or who are sensitized should not use this product.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Medical Conditions Generally Aggravated by Exposure

Allergy , skin disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - Promptly wash with soap and water. Do not wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Not a likely route of entry. Although this product is not known to cause respiratory problems, if breathing is difficult remove to fresh air and provide oxygen

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust away from applicator.		

Protective Gloves	Natural Rubber or Neoprene	Eye Protection	Splash goggles or face shield.
-------------------	----------------------------	----------------	--------------------------------

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate, clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams may help, but gloves must still be worn. Clean-up with soap and water. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.

Waste Disposal Method:

Dispose in accordance with Federal, State and Local requirements.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use.

Other Precautions None known.

Prepared by Murty Bhamidipati - Chemist

PLEASE

"The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH

NOTE

RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."